

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
IP CAMERA				
1	TITAN 5000PWSF-SAF-NF	1/3" 5.0 Megapixel Starlight CMOS Sensor H.265/H.264 Encoding, Dual Stream 2.8mm F1.6 Starlight Advance Fixed lens Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps Built in Microphone Digital WDR, 3DNR, HLC, BLC 30m Warmlight, 3 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR Human Body Detection IP67 Metal Case, Easy Installation, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		21,650,000
IP CAMERA				
2	TITAN 5000PWSF-SAF-IF	1/3" 5.0 Megapixel Starlight CMOS Sensor H.265+/H.264 Encoding, Dual Stream 2.8mm F1.6 Starlight Advance Fixed Lens Main Stream 5MP (2880*1620) @ 25fps Built in Microphone Digital WDR, 3DNR, HLC, BLC 30m Warmlight, 3 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR SMD (Human/Vehicle Detection), Perimeter, Tripwire IP67 Metal Case, Easy Installation, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		21,650,000
SMD Smart Motion Detection				
IP CAMERA				
3	TITAN 5100PWSF-SAF-IF	1/2.7" 5.0 Megapixel Starlight CMOS Sensor, 16:9 Ratio H.265+/H.264 Encoding, Dual Stream 2.8mm F1.6 Starlight Advance Fixed Lens Main Stream 5MP (2880*1620) @ 25fps Built in Microphone 120db WDR, 3DNR, HLC, BLC 30m Warmlight, 3 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR SMD (Human/Vehicle Detection), Face Detection, Perimeter, Tripwire IP67 Metal Case, Easy Installation, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		27,800,000
SMD Smart Motion Detection				
IP CAMERA				
4	AWASIS 5000PWLF-SAF-NF	1/3" 5.0 Megapixel Starlight CMOS Sensor H.265/H.264 Encoding, Dual Stream 3.6mm F1.6 Starlight Advance Fixed lens Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps Built in Microphone Digital WDR, 3DNR, HLC, BLC 30m Warmlight, 3 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR Human Body Detection IP67 Metal Case, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		20,500,000
IP CAMERA				
5	KAVARIA 5000PWLF-SAF-NF	1/3" 5.0 Megapixel Starlight CMOS Sensor H.265/H.264 Encoding, Dual Stream 3.6mm F1.6 Starlight Advance Fixed lens Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps Built in Microphone Digital WDR, 3DNR, HLC, BLC 50m Warmlight, 4 EXIR Power LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR Human Body Detection IP67 Metal Case, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		23,850,000
IP CAMERA				
6	POLARIS 5000PWLF-SAF-IF	1/3" 5.0 Megapixel Starlight CMOS Sensor H.265+/H.264 Encoding, Dual Stream 3.6mm F1.6 Starlight Advance Fixed Lens Main Stream 5MP (2880*1620) @ 25fps Built in Microphone Digital WDR, 3DNR, HLC, BLC 40m Warmlight, 4 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR SMD (Human/Vehicle Detection), Perimeter, Tripwire IP67 Metal Case, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		21,000,000
SMD Smart Motion Detection				
IP CAMERA				
7	NESTOR 8100PWLF-SAF-IF	1/2.8" 8.0 Megapixel SONY STARVIS IMX415 Sensor H.265+/H.264 Encoding, Dual Stream 3.6mm F1.6 Starlight Advance Fixed Lens Main Stream 8MP (3840*2160) @ 20fps Built in Microphone 120db WDR, 3DNR, HLC, BLC 40m Warmlight, 4 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR SMD (Human/Vehicle Detection), Face Detection, Perimeter, Tripwire IP67 Metal Case, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		39,700,000
SMD Smart Motion Detection				
IP CAMERA				
8	KAVARIA 8100PWLF-SAF-IF	1/2.8" 8.0 Megapixel SONY STARVIS IMX415 Sensor H.265+/H.264 Encoding, Dual Stream 3.6mm F1.6 Starlight Advance Fixed Lens Main Stream 8MP (3840*2160) @ 20fps Built in Microphone 120db WDR, 3DNR, HLC, BLC 50m Warmlight, 4 EXIR Power LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR & NVR SMD (Human/Vehicle Detection), Face Detection, Perimeter, Tripwire IP67 Metal Case, 12VDC, Smart PoE Fara View Mobile Monitoring, VMS Monitoring		42,700,000
SMD Smart Motion Detection				

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
9	METIS 200ASF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, High Power LED OSD Menu by UTC (output 4-in-1)		6,850,000
10	DEVRA 200ASF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, High Power LED OSD Menu by UTC (output 4-in-1)		6,750,000
11	DEVRA 200ASF-SLA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 24 SMD LED Built in MIC OSD Menu by UTC (output 4-in-1)		8,150,000
12	 DEVRA 200DSF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED Built in MIC OSD Menu by UTC (output 4-in-1)		9,900,000
13	 DEVRA 200DSF-SCA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED Built in MIC, Support Audio In TVI & CVI Mode (Compatible With Dahua Recorder) OSD Menu by UTC (output 4-in-1)	 	9,900,000
14	NORMA 200ASF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 24 LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		8,750,000
15	NORMA 200ASF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 24 SMD LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		9,150,000
16	 NORMA 200WSF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Exir LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,950,000
17	 NORMA 200WSF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Exir LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		11,500,000
18	 NORMA 500WSF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Exir LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		14,850,000
19	 DORIS 200WSF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight Length, 4 Array LED OSD Menu by UTC (output 4-in-1) Built in MIC		9,260,000
20	 LARIS 500DSF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 50m IR Length, 4 Dual LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Ball		15,200,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
21	ARTEMIS 200ASF-SL	1/2.9" CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed Lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC OSD Menu by UTC (output 4-in-1) 45m IR Length, 24 SMD LED IP66, Metal Case		9,430,000
22	TITAN 200DSF-SCA	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight- 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC, Support Audio In TVI & CVI Mode (Compatible With Dahua Recorder) IP67, Metal Ball, Easy Installation		12,900,000
23	TITAN 200DSF-SA	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight- 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP67, Metal Ball, Easy Installation		12,900,000
24	TITAN 500DSF-SA	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 2.8mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight- 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP67, Metal Ball, Easy Installation		15,650,000
25	TITAN 200WSF-SCA	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC, Support Audio In TVI & CVI Mode (Compatible With Dahua Recorder) IP67, Metal Ball, Easy Installation		12,200,000
26	TITAN 500WSF-SA	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 2.8mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight, 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP67, Metal Ball, Easy Installation		15,100,000
27	POLARIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight, 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case, Easy Installation		12,000,000
28	POLARIS 500WLF-SA	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight, 4 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		15,450,000
29	NESTOR 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight, 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,000,000
30	NESTOR 500WLF-SA	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight, 4 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		15,450,000
31	NESTOR 200DLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length, 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,550,000
32	NESTOR 500DLF-SA	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length, 4 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		16,000,000



ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
33	 NESTOR 500DLF-S	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length, 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		15,550,000
34	 HELIX 200WLF-S/28	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case	 	11,300,000
35	 HELIX 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,300,000
36	 HELIX 200WLF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		11,750,000
37	 HELIX 200DLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,750,000
38	 HELIX 500DLF-SA	1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case	 	15,200,000
39	 HELIX 500DLF-S	1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		14,750,000
40	 HELIX 500WLF-SA	 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight, 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		14,600,000
41	 AWASIS 200DLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,000,000
42	 AWASIS 500DLF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		15,450,000
43	 AWASIS 500WLF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight, 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		14,850,000
44	 AWASIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 Exir LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,500,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
45	 AWASIS 500WLF-S	1/2.5" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,800,000
46	 Callisto 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 4 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,950,000
47	 Callisto 500WLF-S	1/2.5" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 4 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,250,000
48	CAPELLA 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6 mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 35~40m IR Length, 6 Mini Array OSD Menu by UTC(output 4-in-1) IP66, Metal Case		8,800,000
49	CAPELLA 200ALF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6 mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 35~40m IR Length, 6 Mini Array OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,000,000
50	 CAPELLA 500ALF-S	1/2.5" Starlight Image Sensor, 5.0 Megapixel 3.6 mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 35~40m IR Length, 6 Mini Array IP66, Metal Case		12,600,000
51	 ERIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,000,000
52	 ERINOM 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 25~30m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,100,000
53	PARSIS 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30~35m IR Length, 6 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		8,800,000
54	PARSIS 200ALF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30~35m IR Length, 6 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,000,000
55	 PARSIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 6 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,550,000
56	 PARSIS 500WLF-S	1/2.5" Starlight Image Sensor, 5.0 Megapixel 3.6 mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 30m Warmlight Length, 6 Array LED IP66, Metal Case		12,950,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
57	NARSIS 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40~45m IR Length, 8 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,850,000
58	NARSIS 200ALF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40~45m IR Length, 8 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,150,000
59	 NARSIS 500ALF-S	1/2.5" Starlight Image Sensor, 5.0 Megapixel 3.6 mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 40~45m IR Length, 8 Array LED IP66, Metal Case		12,550,000
60	AVILON 200ALV-E	1/2.9" CMOS Sensor, 2.0 Megapixel 2.8~12mm Varifocal lens Resolution 1932(H) × 1088(V) DWDR, 3DNR, AWB, BLC 50~60m IR Length OSD Menu by UTC(output 4-in-1) IP66, Metal Case		16,850,000
61	AVILON 500ALV-E	1/2.5" CMOS Sensor, 5.0 Megapixel 2.8~12 mm Varifocal lens Resolution 2608(H) × 1952(V) DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 50~60m IR Length IP66, Metal Case		21,650,000
62	 NESO 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 60m Warmlight Length, 8 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,700,000
63	 KAVARIA 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 50m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,800,000
64	 KAVARIA 500WLF-S	1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 50m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		16,100,000
65	 KAVARIA 200ALF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 70~80m IR Length , High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,750,000
66	 KAVARIA 500ALF-S	1/2.5" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC 70~80m IR Length , High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		14,750,000
67	FARA AI ALARM BOX	3 Output Relay Box 1 Output With 12VDC 1 RJ45 Web Management Interface Compatible With Z Series XVR 12VDC Input (Without Adaptor) این محصول به وسیله کابل شبکه به رکوردرهای سری زد متصل شده و با تعریف و پیاده سازی سناریوهای مختلف از طریق رکوردر و منوی خود محصول می توان از قابلیت های تشخیص آسان و خودروی دوربین و رکوردر در جهت فعال سازی خروجی محصول استفاده نمود تا خروجی تجهیزات از قبیل آژیر، تلفن کننده، فرمان به دردیگر و سایر تجهیزات فرمان پذیر را فعل کرد و از دوربین ها به عنوان دکتور محیطی با هوش مصنوعی و دقت بسیار بالا استفاده نمود		13,800,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
68	OHD-6104XF-A1	4CH H.265 5MP-Lite XVR 4CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode) Preview Capacity: 4*(5MP-Lite@20fps/4MP-Lite@25fps/1080P@25fps) Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@18fps/1080P-Lite@25fps) 4CH Playback Support AOC (Audio Over Coaxial For All Channel) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Output 1 SATA HDD Up to 8TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod Mobile APP & CMS PC Software		22,900,000
69	OHD-4104ZF-A1	4CH H.265 1080P-Lite XVR Preview Capacity: 4*1080P-Lite@25fps Code Capacity: 4*1080P-Lite@24fps 2CH Playback Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers		20,900,000
70	OHD-6104ZF-A1	 SMD  4CH AHD H.265 5MP-Lite XVR 4CH AHD Camera + 1CH IP Camera Preview Capacity: 4*5MP-Lite@20fps Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@15fps/1080P-Lite@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App Adaptive Iran & International Servers		25,400,000
71	OHD-6104ZFN-A1	 SMD  4CH H.265 5MP-Lite XVR 4CH Camera + 1CH IP Camera Preview Capacity: 4*5MP-Lite@20fps Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@15fps/1080P-Lite@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers		25,400,000
72	OHD-8104ZHN-4KL/A4	 SMD   4CH H.265 4K-Lite & Real 5MP XVR 4CH Camera (Analog & IP) Preview Capacity: 4*(8MP-Lite@15fps/5MP@12fps) Code Capacity: 4*(8MP-Lite@15fps/5MP@12fps/4MP@15fps/1080P@25fps) 4CH Playback (2CH@15fps + 2CH@1fps) Support SMD (Human/Vehicle Classification For 4CH) Support Face Detection Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers	 	36,900,000
73	OHD-8104ZFN-4KL/A4	SMD  4CH H.265 Real 5MP XVR 4CH Camera (Analog & IP) Preview Capacity: 4*5MP@12fps Code Capacity: 4*(5MP@12fps/4MP@15fps/1080P@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support Face Detection Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers		35,700,000
74	OHD-8104ZF-4KL/A4	SMD  4CH H.265 Real 5MP XVR 4CH Camera (Analog & IP) Preview Capacity: 4*5MP@12fps Code Capacity: 4*(5MP@12fps/4MP@15fps/1080P@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers		35,700,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
75	OHD-6104XH-A1	4CH H.265 5MP-Lite XVR 4CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:4*(5MP-Lite@20fps/4MP-Lite@25fps/1080P@25fps) Code Capacity: 4*(5MP-Lite@8fps/4MP-Lite@15fps/1080P@18fps/1080P-Lite@25fps) 4CH Playback Support real-time face detection, Face list, Face playback Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI & VGA Video Output 1 SATA HDD Up to 6TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP & CMS PC Software		25,400,000
76	OHD-6108XF-A1	8CH H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode) Preview Capacity: 8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity: 8*(5MP-Lite@5fps/4MP-Lite@8fps/1080P-Lite@15fps) 8CH Playback Support AOC (Audio Over Coaxial For All Channel) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI & VGA Video Output 1 SATA HDD Up to 8TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod Mobile APP & CMS PC Software		28,750,000
77	OHD-6108ZF-A1	 SMD  8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera + 2CH IP Camera Preview Capacity: 8*5MP-Lite@12fps Code Capacity: 8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 8CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App Adaptive Iran & International Servers		32,800,000
78	OHD-6108ZFU-A1 New Ultra Model	 SMD  8CH H.265 5MP-Lite XVR 8CH Camera + 2CH IP Camera Preview Capacity: 8*5MP-Lite@12fps Code Capacity: 8*(5MP-Lite@12fps/1080P-Lite@16fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection 1CH Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers	 	32,800,000
79	OHD-6108ZFN-A1	 SMD  8CH H.265 5MP-Lite XVR 8CH Camera + 2CH IP Camera Preview Capacity: 8*5MP-Lite@12fps Code Capacity: 8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers		32,800,000
80	OHD-8108ZFN-4KL/A4	 SMD  8CH H.265 4K-Lite & Real 5MP XVR 8CH Camera + 2CH IP Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps) Code Capacity: 8*(4K-Lite@9fps/5MP@8fps/4MP@10fps/1080P@20fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers		52,350,000
81	OHD-8108ZHN-4KL/A4	 SMD   HISILICON NEW AI Chipset 8CH H.265 4K-Lite & Real 5MP XVR 8CH Camera (Analog & IP) Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps) Code Capacity: 8*(4K-Lite@9fps/5MP@8fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers	 	52,350,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
				
82	OHD-8208ZF-4KL/A4	8CH H.265 4K-Lite & Real 5MP XVR 8CH Camera + 2CH IP Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps) Code Capacity: 8*(4K-Lite@9fps/5MP@8fps/4MP@10fps/1080P@20fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 2 SATA HDD Up to 10TB For each port (Change Adaptor to 12V/5A) 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers		52,350,000
83	OHD-6108XH-A1	8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity:8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps) 8CH Playback:4ch main stream/8ch sub-stream Support real-time face detection, Face list, Face playback Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Output 1 SATA HDD Up to 6TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP & CMS PC Software		33,150,000
84	OHD-6108XH-A4	8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity:8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps) 8CH Playback:4ch main stream/8ch sub-stream Support real-time face detection, Face list, Face playback Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Output 1 SATA HDD Up to 6TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP & CMS PC Software		33,600,000
				
85	OHD-6216ZF-A1	16CH AHD H.265 5MP-Lite XVR 16CH AHD Camera + 4CH IP Camera Preview Capacity:16*5MP-Lite@12fps Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 16CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 2 SATA HDD Up to 10TB for each port 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod FARA VIEW App Adaptive Iran & International Servers		56,950,000
				
86	OHD-6116ZFN-A1	16CH H.265 5MP-Lite XVR 16CH Camera + 4CH IP Camera Preview Capacity:16*5MP-Lite@12fps Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers		56,200,000
  NEW AI Chipset				
87	OHD-6108ZHN-A4	8CH H.265 5MP-Lite XVR 8CH Camera (Analog & IP) Preview Capacity: 8*5MP-Lite@20fps Code Capacity: 8*(5MP-Lite@12fps) 8CH Playback (4CH@12fps + 4CH@1fps) Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB - 1*10/100 Mbps LAN Interface P2P support, Onvif, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers	NEW 	35,900,000
  NEW AI Chipset				
88	OHD-8116ZHN-4KL/A4	16CH H.265 4K-Lite & Real 5MP XVR 16CH Camera (Analog & IP) Preview Capacity: 16*(4K-Lite@15fps/5MP@12fps) Code Capacity: 16*(4K-Lite@7fps/5MP@8fps) 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support 1CH face detection Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers	NEW 	79,350,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
			NEW	
89	OHD-8232ZHN-4KL/A4	SMD HISILICON NEW AI Chipset 32CH H.265 4K-Lite & Real 5MP XVR 32CH Camera (Analog & IP) Preview Capacity: 32*(4K-Lite@15fps/5MP@12fps) Code Capacity: 32*(4K-Lite@7fps/5MP@6fps) 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support Face Detection Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC) 2 SATA HDD Each Up to 10TB 4/1 Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers		174,000,000
90	OHD-6216XH-A4	16CH H.265 5MP-Lite XVR 16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:16*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps) 16CH Playback Support real-time face detection, Face list and Face playback Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Output 2 SATA HDD Up to 6TB for each port 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP & CMS PC Software		56,950,000
91	OHD-8216X-A2	AI 16CH H.265 8MP-Lite XVR 16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity: 16*(8MP-Lite@15fps/5MP@12fps/5MP-Lite@20fps/1080P@25fps) Code Capacity: 16*(8MP-Lite@8fps/5MP@6fps/5MP-Lite@12fps/1080P@15fps) 16CH Playback Support real-time face detection, Face list and Face playback AI Functions: Intrusion , Line crossing Support Phone push on Mobile app Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI & VGA Video Output 2 SATA HDD Up to 6TB for each port 2/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP & CMS PC Software Wireless Mouse		78,200,000